



HGL5-12

12-Volt,5AH@20HR

Valve Regulated
Lead-Acid Battery

Design for Standby
Power Applications

Life Expectancy:	Application
Expected trickle life: 3-5 years at 25°C.	UPS, Fishing Lights, Emergency Lights, Lawn Mowers, Video Camcorders(VCR).


Specifications	
Nominal Voltage	12V(6 cells per unit)
Rated Capacity	5.0AH @20HR-Rate to 1.75V per cell@25°C
	4.65AH @10HR-Rate to 1.75V per cell@25°C
	4.25AH @5HR-Rate to 1.70V per cell@25°C
	3.0AH @1HR-Rate to 1.60V per cell@25°C
Weight	Approx.1.48kg (3.26lbs.)
Max. Discharge Current with standard terminal	40 A
Max. Short-Duration Discharge Current	75 A (5S)
Internal Resistance of charged battery	Approx. 40 mΩ
Short Circuit Current	310 A

Mechanical Specifications		
Overall Height (H)	107mm	4.21"
Container Height (h)	101mm	3.98"
Length	90mm	3.54"
Width	70mm	2.76"
Terminal	Standard	F1 (Quick Disconnect .187)
	Optional	F2 (Quick Disconnect .250)
Container Material	Standard	ABS (UL 94-HB)
	Optional	ABS Flame Retardant (UL94-VO)
Sealed Construction	Can be operated in any position without leakage.	

Operating Temperature Range		
Nominal Operating Temperature	25°C (77°F)	
Discharge	-15°C ~+ 50°C	5°F~122°F
Charge	-15°C ~ +40°C	5°F~104°F
Storage	-15°C ~ +40°C	5°F~104°F
Self discharge(25°C)	Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F);Fully recharging is required before usage, For higher temperatures the time interval will be shorter.	

Charge Characteristics		
Trickle use	Initial current	0.75 A or smaller
	Control Voltage	13.5 to 13.8 VDC/unit@ (25°C)
Cycle use	Initial current	2.0 A or smaller
	Control Voltage	14.40~14.9VDC/unit (25°C)
Charging Temperature Compensation	Cycle use	-4mV/cell/°C
	Float use	-3mV/cell/°C
CAUTION : Do not charge in a sealed container.		

DIMENSIONS (All units shown in mm)




Constant Current Discharge Rating Amperes @ 77°F (25°C)											
Cut off voltage V/cell	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	20H
1.75V	7.52	4.94	3.49	2.88	1.64	1.23	0.85	0.569	0.465	0.396	0.250


Note The above data are average values, and can be obtained with 3 charge/discharge cycles. These are not minimum values.




Discharge Characteristic Curves at 25°C (77°F)




Temperature Effects In Relation to Battery Capacity




Capacity Retention Characteristic



State of Charge (SOC) vs Open Circuit Voltage (OCV)



Cycle Life vs. Depth of Discharge (DOD)



Float Service Life

